

SPECIFICATION (Russian)
FUEL JP54 GOST 10227 – 86

PROPERTIES	UNIT	RESULT	TEST- IP	METHOD	ASTM
ADDITIVES					
Antioxidant in hydro processed fuel	Mg/I	Min	17		
Antioxidant non-hydro processed fuel	Mg/I	Max	24		
Static dissipater first doping ASA-3	Mg/I	Min	24		
Stadis 450	Mg/I	Min	1		
COMBUSTION PROPERTIES					
Smoke point	mj/lkg	Min	18.4		D4808
Specific energy, net	Mm	Min	19		D1322
Luminomitter number		Min	45		D1740
Naphthalenes	% volume	Max	3		D1840
COMPOSITION					
Total, Acidity	mg KOH/g	Max	0.01	354	D3242
Aromatics	% vol	Max	22	158	D1318
Sulphur, Total	% mass	Max	0.30	107	D1266/2622
Sulphur, Mercaptan	% mass	Max	0.003	342	D3227
Doctor, test				30	D4952
VOLATILITY					
Initial Boiling Point	Centigrade	Max	Report	123	D96
10% vol at C			240		
20% vol at C			Report		
50% vol at C			Report		
80% vol at C			Report		
End point	Centigrade	Max	300		
Recovered residuals	% Vol	Max	1.5		
Loss	% Vol	Max	1.5		
Flash Point	Centigrade	Max	42	170/303	D56/3828
Density at 15 C	Kg/m2	min/max	776/840	180/305	D1256
LOW TEMPERATURE					
Freezing Point	Centigrade	Max	-40	15	D2256
CORROSION					
Corrosion, copper (2hrs at 100C)		Max	1	154	D130
Corrosion, silver (4hrs at 50C)		Max	1	227	
Thermal stability control, Temp. 280C					
Filter pressure, differential mm.Hg		Max	323		
Tube deposit rating (visual)		Max	25	<3	
CONTAMINATIONS					
Existent Gum	mg/100ml	Max	7	131	D361
Water reaction, interface rating		Max	16	258	D1084
Fuel with static dissipater additives		Min	75		D3648
Fuel without static dissipater additive		Min	85		
Electrical conductivity	p ³ /m		Report		